

# Premium Performance

PREMIUM

MID-RANGE

ECONOMY

PREMIUM MATERIALS HANDLING RESILIENT

**TRELLEBORG**  
**M<sup>2</sup>**



PREMIUM MATERIALS HANDLING RESILIENT

TRELLEBORG M2

Trelleborg M<sup>2</sup> is a premium, solid, resilient tire designed for demanding materials handling environments. For forklift trucks that are in heavy use or routinely carrying heavy loads, Trelleborg M<sup>2</sup>'s design and construction ensures maximum performance.

Trelleborg M<sup>2</sup> resilient tires feature the Pit Stop Line wear indicator. The Pit Stop Line ensures that users get maximum whole-life value from their choice of tire by always replacing them at the right time and being able to keep forklift downtime to a minimum, as well as always knowing that their tires are safe to use.



| Tire Size | Alternative Size    | Rim Size  | Additional Pattern | LOC | Tire Dimensions [mm] |               | Load Capacity [kg] |                               |                |
|-----------|---------------------|-----------|--------------------|-----|----------------------|---------------|--------------------|-------------------------------|----------------|
|           |                     |           |                    |     |                      |               | Static             | Forklift trucks up to 25 km/h |                |
|           |                     |           |                    |     | Overall Diameter     | Section Width |                    | Load Wheel                    | Steering Wheel |
| 10½x4-6*  |                     | 3.25I-6   | Ribbed only        |     | 268                  | 104           | 710                | 610                           | 470            |
| 4.00-8    |                     | 2.50-8    | Ribbed             |     | 408                  | 104           | 1100               | 950                           | 730            |
| 4.00-8    |                     | 3.00D-8   | Ribbed             | •   | 408                  | 104           | 1100               | 950                           | 730            |
| 4.00-8 *  |                     | 3.56-8    | Ribbed only        |     | 408                  | 125           | 1170               | 1010                          | 775            |
| 4.00-8    |                     | 3.75P-8   |                    |     | 408                  | 125           | 1170               | 1010                          | 775            |
| 15x4½-8   | 125/75-8            | 3.00D-8   | Ribbed             | •   | 376                  | 117           | 1210               | 1040                          | 800            |
| 5.00-8    |                     | 3.00D-8   |                    | •   | 457                  | 122           | 1650               | 1415                          | 1090           |
| 5.00-8    |                     | 3.75P-8   | Ribbed             |     | 457                  | 152           | 1740               | 1495                          | 1150           |
| 16x6-8    | 150/75-8            | 4.33R-8   | Ribbed             | •   | 411                  | 152           | 1740               | 1495                          | 1150           |
| 17x7-8 *  |                     | 4.33R-8   | Smooth only        |     | 430                  | 159           | 2160               | 1860                          | 1430           |
| 18x7-8    | 180/70-8            | 4.33R-8   |                    | •   | 457                  | 157           | 2490               | 2145                          | 1650           |
| 18x9-8    |                     | 7.00-8    | Smooth             |     | 457                  | 207           | 2870               | 2470                          | 1900           |
| 140/55-9  | 15x5.5-9            | 4.00E-09  |                    | •   | 373                  | 132           | 1360               | 1170                          | 900            |
| 6.00-9    |                     | 4.00E-09  |                    | •   | 526                  | 140           | 2190               | 1885                          | 1450           |
| 6.00-9    |                     | 4.00E-09  | Ribbed             |     | 526                  | 140           | 2190               | 1885                          | 1450           |
| 21x8-9    | 200/75-9            | 6.00E-09  |                    | •   | 518                  | 185           | 3200               | 2755                          | 2120           |
| 6.50-10   |                     | 5.00F-10  |                    | •   | 577                  | 160           | 2720               | 2340                          | 1800           |
| 6.50-10   |                     | 5.50F-10  |                    |     | 577                  | 160           | 2720               | 2340                          | 1800           |
| 180/60-10 |                     | 5.00F-10  |                    | •   | 458                  | 157           | 2795               | 2410                          | 1850           |
| 200/50-10 |                     | 6.50F-10  |                    | •   | 456                  | 197           | 2870               | 2470                          | 1900           |
| 23x9-10   | 225/75-10           | 6.50F-10  |                    | •   | 584                  | 201           | 4000               | 3445                          | 2650           |
| 7.00-12   |                     | 5.00S-12  | Smooth             | •   | 650                  | 173           | 3380               | 2920                          | 2240           |
| 23x10-12  | 250/60-12           | 8.00G-12  |                    | •   | 587                  | 239           | 4380               | 3770                          | 2900           |
| 27x10-12  | 250/75-12           | 8.00G-12  |                    | •   | 678                  | 239           | 4530               | 3900                          | 3000           |
| 315/45-12 |                     | 10.00G-12 |                    | •   | 572                  | 279           | 5210               | 4485                          | 3450           |
| 7.00-15   | 29x8-15             | 5.5-15    |                    | •   | 729                  | 180           | 4115               | 3545                          | 2725           |
| 7.50-15   |                     | 5.5-15    |                    |     | 747                  | 193           | 4530               | 3900                          | 3000           |
| 7.50-15   |                     | 6.5-15    |                    |     | 747                  | 193           | 4530               | 3900                          | 3000           |
| 8.25-15   |                     | 5.5-15    |                    |     | 808                  | 208           | 5360               | 4615                          | 3550           |
| 8.25-15   |                     | 6.5-15    |                    | •   | 808                  | 208           | 5510               | 4750                          | 3650           |
| 28x9-15   | 225/75-15           | 6.5-15    |                    |     | 693                  | 224           | 4530               | 3900                          | 3000           |
| 28x9-15   | 225/75-15 (8.15-15) | 7.0-15    |                    | •   | 693                  | 224           | 4530               | 3900                          | 3000           |

THE PIT STOP LINE

Choosing Pit Stop Line tires ensures that customers always get maximum value by replacing tires at the right time. As the tire tread wears down, a highly visible orange stripe appears on the tire surface indicating approximately 100 hours of tire life remaining. This allows ample time to schedule replacement at your convenience without compromising performance, safety or productivity.



| Tire Size | Alternative Size   | Rim Size | Additional Pattern | LOC | Tire Dimensions [mm] |               | Load Capacity [kg] |                               |                |
|-----------|--------------------|----------|--------------------|-----|----------------------|---------------|--------------------|-------------------------------|----------------|
|           |                    |          |                    |     |                      |               | Static             | Forklift trucks up to 25 km/h |                |
|           |                    |          |                    |     | Overall Diameter     | Section Width |                    | Load Wheel                    | Steering Wheel |
| 250-15    | 250/70-15          | 7.0-15   |                    | •   | 711                  | 221           | 5510               | 4745                          | 3650           |
| 250-15    | 250/70-15          | 7.5-15   |                    |     | 711                  | 221           | 5510               | 4745                          | 3650           |
| 280/50-15 |                    | 8.0-15   | Ribbed             | •   | 670                  | 255           | 6040               | 5200                          | 4000           |
| 300-15    | 315/70-15          | 8.0-15   |                    | •   | 813                  | 257           | 6795               | 5850                          | 4500           |
| 400/60-15 |                    | 11.0-15  | VP15 only          |     | 815                  | 325           | 10420              | 8970                          | 6900           |
| 355/45-15 | 28x12½-15          | 9.75-15  |                    | •   | 683                  | 288           | 6610               | 5690                          | 4375           |
| 355/50-15 |                    | 9.75-15  |                    | •   | 711                  | 284           | 6610               | 5690                          | 4375           |
| 355/65-15 | 32x12½-15 (350-15) | 9.75-15  |                    | •   | 808                  | 282           | 9060               | 7800                          | 6000           |
| 7.50-16   |                    | 5.5-16   |                    |     | 808                  | 208           | 4645               | 4000                          | 3075           |
| 9.00-20   |                    | 6.5-20   |                    |     | 973                  | 221           | 6795               | 5400                          | 4500           |
| 10.00-20  | 270/95-20          | 6.5-20   |                    |     | 1011                 | 249           | 7360               | 5850                          | 4875           |
| 10.00-20  | 290/95-20          | 8.0-20   |                    |     | 1011                 | 249           | 7550               | 6000                          | 5000           |
| 12.00-20  | 290/95-20          | 8.0-20   | Smooth             |     | 1092                 | 259           | 9515               | 7560                          | 6300           |
| 12.00-20  | 330/95-20          | 8.5-20   |                    |     | 1092                 | 259           | 9515               | 7560                          | 6300           |
| 12.00-20  | 330/95-20          | 10.0-20  | Smooth             |     | 1090                 | 312           | 9815               | 7800                          | 6500           |
| 355/50-20 |                    | 10.0-20  | Smooth             | •   | 833                  | 310           | 10420              | 8970                          | 6900           |

\* Traction pattern not available

SPECIAL COMPOUNDS AVAILABLE

NM

Non-Marking

EC

Electrically Conductive

HL

High Load


CR

Cut Resistant

SC

Chemical Resistant (Scrubber)

TREAD PATTERNS



# Five reasons to choose Pit Stop Line



## MAXIMUM VALUE

Choosing Pit Stop Line means never replacing tires too early and always being in control of tire spend.



## MAXIMUM UPTIME

Pit Stop Line tires are built to perform and last. Premium design, construction and compounding increase productivity.



## ENHANCED SAFETY

Choosing Pit Stop Line tires means never replacing tires too late, protecting operators and machines.



## REDUCED IMPACT

Choosing Pit Stop Line tires means using fewer tires and reducing carbon footprint.



## SERVICE MADE EASY

Choosing Pit Stop Line tires means having plenty of time to schedule replacement at the right time.



TRELLEBORG